

# GMG

Global Machinery Group, Inc.

# 3394-RT-T / 6094-RT

## ULTRA-DECK ROUGH TERRAIN SCISSOR LIFT



### STANDARD FEATURES:

- Extreme tilt angles (3394-RT T)
- Unmatched travel speeds
- Quiet mode feature
- Up to 2,755 lbs (1250 kg) Platform lift capacity at full height
- 7.55m Ultra-Deck platform fully extended
- Auto / Manual leveling outriggers
- Oscillating axle for optimum traction
- 4wd Rough terrain auto select
- Kubota diesel
- Multiple disc brakes
- 2 year warranty

## 3394-RT T WORLD'S FASTEST LIFT

Designed specifically for tunneling/mining applications

### 3394-RT Tunnel UNMATCHED TRAVEL SPEEDS WITH EXTREME TILT ANGLES

- Stowed Height: 6.2 mph (10km/h)
- 13' (4m) Height: 3.1 mph (5.0km/h) drive speed / up to 9° tilt
- 20' (6m) Height: 2.5 mph (4.0km/h) drive speed / up to 8° tilt
- 26' (8m) Height: 2.0 mph (3.0km/h) drive speed / up to 5° tilt
- 33' (10m) Height: 1.3 mph (2.0km/h) drive speed / up to 4° tilt

**EXTREME GRADE  
FOR HEAVY CONSTRUCTION USE**

[www.goGMG.com](http://www.goGMG.com)



MODELS	3394-RT T		6094-RT	
	US	Metric	US	Metric
<b>Measurements</b>				
Working height maximum	39'	11.9 m	66'	20.1 m
Platform height maximum	33'	10 m	60'	18.2 m
Platform height - stowed platform floor	6'7"	2.02 m	6'7"	2.02 m
Platform length - retracted	17'5"	5.23 m	17'5"	5.23 m
- extended	24'10"	7.55 m	24'10"	7.55 m
Platform width - outside	75"	1.9 m	75"	1.9 m
Toeboard height	6"	0.15 m	6"	0.15 m
Height - stowed	122"	3.09 m	122"	3.09 m
rails lowered	92"	2.33 m	92"	2.33 m
Length stowed	17' 5"	5.23 m	17' 5"	5.23 m
Width	94"	2.38 m	94"	2.38 m
Wheelbase	113"	2.87 m	113"	2.87 m
Ground clearance - center	15"	38 cm	15"	38 cm

<b>Productivity</b>				
Maximum platform occupancy	5		4	
Lifting capacity	2,755 lbs	1250 kg	1,200 lbs	540 kg
Extension deck capacity (each deck)	500 lbs	227 kg	500 lbs	227 kg
Drive height	full height		40'	12m
Gradeability - stowed	45%			
Turning radius - inside	82"	2.08 m	82"	2.08 m
Turning radius - outside	16.8'	5.12 m	16.8'	5.12 m
Raise speed	36 seconds		60 seconds	
Lower speed	31 seconds		55 seconds	
Controls	fully proportional			
Drive	four wheel			
Tires - rough terrain	33 x 12 in		84 x 30 cm	

<b>Power</b>				
Power source	Kubota Diesel Engine			
Fuel tank capacity	30 gal / 113.6 L			
Hydraulic system capacity	30 gal / 133.6 L			

<b>Weight</b>				
Standard	16,450 lbs	7462 kg	20,450 lbs	9276 kg

<b>3394-RT Tunnel Speeds &amp; Angles</b>	Drive Speed	Tilt Angles
Stowed Height	10 km/h	
4m Height	5 km/h	Up to 9°
6m Height	4 km/h	Up to 8°
8m Height	3 km/h	Up to 5°
10m Height	2 km/h	Up to 4°

## 3394-RT TUNNEL



in action

### 3394-RT Tunnel Machine SLOPE ANGLE OPERATION

#### 13' (4m) Height:

##### Fore and Aft direction:

- °8 Amber light comes on, alarm sounds, Lift/Drive continues
- °9 Red light comes on, alarm sounds, Lift/Drive interrupted

##### Side and Side direction:

- °7 Amber light comes on, alarm sounds, Lift/Drive continues
- °8 Red light comes on, alarm sounds, Lift/Drive interrupted

#### 20' (6m) Height:

##### Fore and Aft direction:

- °7 Amber light comes on, alarm sounds, Lift/Drive continues
- °8 Red light comes on, alarm sounds, Lift/Drive interrupted

##### Side and Side direction:

- °5 Amber light comes on, alarm sounds, Lift/Drive continues
- °6 Red light comes on, alarm sounds, Lift/Drive interrupted

#### 26' (8m) Height:

- °4 Amber light comes on, alarm sounds, Lift/Drive continues
- °5 Red light comes on, alarm sounds, Lift/Drive interrupted

#### 33' (10m) Height:

- °3 Amber light comes on, alarm sounds, Lift/Drive continues
- °4 Red light comes on, alarm sounds, Lift/Drive interrupted

### GMG Corporate Office

3428 Bullock Lane  
San Luis Obispo, CA 93401

Phone: +1.805.303.2066

Toll Free (USA/Canada): +1.800.301.0499

### Distributed By:



www.goGMG.com