


Technical sheet :

MLA 5-60 H-Z



Capacities		Metric
Static tipping load with bucket (straight)		2190 kg
Static tipping load with bucket (full tum)		1694 kg
Static tipping load with forks (straight)		1547 kg
Static tipping load with forks (full tum)		1204 kg
Max. height of bucket pivot point	h35	3.16 m
Reach at max. height		0.43 m
Breakout force with bucket		4329.46 daN
Weight and dimensions		
Unladen weight (with forks) with 4-post canopy		3388 kg
Ground clearance	m4	0.258 m
Overall length to carriage (with hitch)	l11	4.18 m
Wheelbase	y	1744 mm
Overall width of 4 posts canopy	b22	1.23 m
Overall cab width	b4	1.228 m
Overall width (over tyres)	b1	1.479 m
Overall height with 4 posts canopy	h38	2.31 m
Overall height with cab	h17	2.313 m
Tilt-up angle	a4	39.9 °
Tilt-down angle	a5	44.7 °
External turning radius (over tyres)	Wa1	3.205 m
Articulation angle		45 °
Performances		
Crowd		2.52 s
Dump		1.85 s
Engine		
Engine brand		Deutz
Engine model		TD 2.2 L3
Number of cylinders / Capacity of cylinders		3 - 337.82 cm ³
I.C. Engine power rating / Power (kW)		60 Hp / 45.5 kW
Max. torque / Engine rotation		200 Nm / 2400 rpm
Engine cooling system		2 radiators water + hydraulic oil
Transmission		
Transmission type		Hydrostatic
Number of gears (forward / reverse)		2 / 2
Max. travel speed (may vary according to applicable regulations)		28.3 km/h
Differential lock		Machine Lock Rear & front
Parking brake		Manual
Hydraulics		
Hydraulic pump type		Gear pump
Hydraulic flow - Pressure		58.3 l/min / 210 Bar
High-Flow Option (l/min)		72.3 l/min
Drive hydraulic system pressure		420 Bar
Tank capacities		
Hydraulic oil		45 l
Fuel tank		82.50 l
Miscellaneous		
Safety cab homologation		Cab ROPS - FOPS Level 1



Siège Social

430 rue de l'Aubinière - 44150 Ancenis Cedex - France

Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes